

Pertronic Supervised 100-Volt Line Speaker Selection Guide

The following table provides a summary of fire system speakers available from Pertronic Industries in New Zealand.

Products	Dimensions / Fittings	Applications / IP Rating	Tappings	Ordering Code & product colours
	115 x 70.5 x 28.5 mm (H x W x D) Flush-box / Surface-mount	Indoor use	0.2W / 0.7W / 1.1W	PSS1-W (white) PSS1-R (red)
	122 x 31 mm (Diameter x H) Surface-mount	Indoor use	0.2W / 0.7W / 1.1W	PSSB401 (white) (includes B401 conventional base) PSSB501 (white) (includes B501AUS AA base)
	136 x 100 mm (Diameter x H) Flush-mount (spring-clip)	Indoor use	0.33W / 0.66W / 1.25W / 3W	PSS3 (white)
	136 X 60 mm (Diameter x H) Flush- / Surface-mount (Use with PSS3-LPSME surface only)	Indoor use	0.33W / 0.66W / 1.25W / 3W	PSS3-LP (white) PSS3-LP-BK (black) PSS3-LPSME (white) PSS3-LPSME-BK (black)
	180 x 100 mm (Diameter x H) Flush-mount (spring-clip)	Indoor use	0.33W / 0.66W / 1.25W / 2.5W / 5W	PSS5 (white) PSS5-BK (black)
	180 x 75 mm (Diameter x H) Flush- / Surface-mount) (Use with PSS5-LPSME surface mount only)	Indoor use	0.33W / 0.66W / 1.25W / 2.5W / 5W	PSS5-LP (white) PSS5-LPSME (white)
	150 x 132 mm (Length x Height) Wall-mount	Indoor use	1W / 3W	PSSHORN (white)
	200 x 230 mm (Diameter x Length) Wall-mount	Indoor / Outdoor use IP66	1.25W / 2.5W / 5W / 7.5W / 10W	BCS-HS10E (grey)
	185 x 245 mm (Diameter x Length) Wall-mount	Outdoor use IP66 (marine grade)	1.25W / 2.5W / 5W / 7.5W / 10W	C2048 (grey)



This information is provided for quick reference. Please refer to the product datasheets and installation notes for complete information.